PMB Moisture Analyser





Speed, Performance, Value - The Right Balance

- Zero adjust facility to enable zero reading
- Built-in memories for storing products and settings
- 3 settings for heating sample fast ramp up, step and standard
- Automatic test start setting for when the lid is closed
- Date and time
- Zero Tracking
- Full range tare
- Quick and easy to configure through the keypad
- Multilingual display
- Large backlit display with dual text prompts
- Capacity tracker
- Security bracket
- · Non-slip adjustable levelling feet

- Colour coded, sealed keypad
- · Large stainless steel pan
- Lock down mounting slot for Kensington™ type lock and cable
- Overload protection
- Splashproof to protect from accidental spills
- Spirit Level
- RS-232 and USB interface
- GLP print outs
- Calibration facilities for temperature and weight
- Mains Power Cord
- Pan lifter to easily remove samples
- Moisture determination
- Weighing









www.adamequipment.com



Technical Specifications

Model	PMB 53	PMB 202
Maximum capacity	50g	200g
Readability	0.001g /0.01%	0.01g /0.05%
Linearity (±)	0.002g	0.02g
Pan size	100mm Ø	

General Specifications

Typical stabilisation time	3 Sec	
Units of measurement	Gram (g), % Moisture / % Solid	
Interface	USB host for memory card and USB I/O interface and RS-232	
Operating temperature	0°C - 40°C	
Calibration	Automatic External	
Display	Backlit LCD display 24mm with dual digits and capacity tracker	
Housing	Aluminium	
Overall dimensions	250 x 360 x 185mm	
(wxdxh)		
Height above pan	30mm	
Net weight	6kg	
Drying temperature	50-160°C increments of 1°C	
range		
Time setting	1 min - 99 mins	
Moisture range	0-100%	
Heater type	Single 400W halogen heater	
Sampling interval time	1 - 59 seconds	
Typical time of	2 - 20 minutes	
measurement		
Power of heaters	400w	

Key Accessories

- · USB Cable
- · Calibration Certficate
- · Security Lock and Cable
- · RS-232 to PC Cable
- Adam DU Data Collection Program
- · In-use Cover
- · Temperature Calibration Kit
- F1 200g Calibration Weight for PMB 202
- F1 50g Calibration Weight for PMB 53
- · ATP Thermal Printer
- · Thermal Paper for ATP







Adam Equipment - offices worldwide