

CORIO CP-1000F Refrigerated – Heating Circulator

Refrigerated Circulators from the CORIO CP range are suitable for applications with a temperature range up to +200°C. The enhanced pump performance ensures they are suitable for easy temperature control tasks in combination with external applications.

Your advantages

- Models for internal and external applications
- Bright, white, easy to read display
- Very quiet
- Easy pump change-over between internal and external circulation
- External pump connections
- Powerful and infinitely adjustable pressure pump
- USB connection
- RS232 interface for online communication
- Space-saving cooling coil design yields more usable space in the bath tank
- Bath lid and drain tap included
- Removable ventilation grid
- Refrigeration unit without side vents
- Class III (FL) according to DIN 12876-1



Technical data

| | | | |
|-----------------------------------|--|------------------------------------|-------------------------|
| Available voltage versions | | Bath | |
| Order No. | 9 013 707 | Bath tank | Stainless steel |
| Available voltage versions: | | Bath cover | integrated |
| 9 013 707.02 | 115V/60Hz (Nema N5-20 Plug) | Usable bath opening cm (W x L / D) | 18 x 13 / 15 |
| 9 013 707.04 | 200-230V/50-60Hz (UK Plug Type BS1363A) | | |
| 9 013 707.05 | 200-230V/50-60Hz (CH Plug Type SEV 1011) | | |
| 9 013 707.33 | 200-230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F) | | |
| 9 013 707.33.chn | 200-230V/50-60Hz (CN Plug) | | |
| Cooling | | Other | |
| Cooling of compressor | 1-stage Air | Classification | Classification III (FL) |
| | | Pump function | Pressure Pump |
| | | Pump type | Immersion Pump |
| Electronics | | Dimensions and volumes | |
| Temperature control | PID1 | Weight kg | 51.5 |
| Absolute temperature calibration | 1 Point Calibration | Barbed fittings inner diameter | 8/12 mm |
| Temperature display | LED | Dimensions cm (W x L x H) | 42 x 49 x 70 |
| Temperature setting | Keypad | Filling volume l | 5 ... 7.5 |
| Electronic Timer hr:min | 0 ... 999 | Pump connections | M16x1 male |
| Temperature values | | | |
| Working temperature range °C | -50 ... 200 | | |
| Temperature stability °C | ±0.03 | | |
| Ambient temperature °C | 5 ... 40 | | |
| Temperature display resolution °C | 0.01 ... 0.1 | | |

Performance values

115V/60Hz (Nema N5-20 Plug)

| 115V/60Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

200-230V/50-60Hz (UK Plug Type BS1363A)

| 200V/50Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| 200V/60Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| 230V/50Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.8 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| 230V/60Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.8 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

200-230V/50-60Hz (CH Plug Type SEV 1011)

| 200V/50Hz | | | | | | | |
|-----------|--|--|--|--|--|--|--|
|-----------|--|--|--|--|--|--|--|

| 200V/60Hz | | | | | | | |
|-----------|--|--|--|--|--|--|--|
|-----------|--|--|--|--|--|--|--|

| | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| 230V/50Hz | | | | | | | |
| Heating capacity kW | 2 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| 230V/60Hz | | | | | | | |
| Heating capacity kW | 2 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

200-230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)

| | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| 200V/50Hz | | | | | | | |
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| | | | | | | | |
|----------------------------|-------|----|------|------|------|------|------|
| 230V/50Hz | | | | | | | |
| Heating capacity kW | 2 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |

| | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| 200V/60Hz | | | | | | | |
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| | | | | | | | |
|----------------------------|-------|----|------|------|------|------|------|
| 230V/60Hz | | | | | | | |
| Heating capacity kW | 2 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |

| | | | |
|------------------------------------|-------------|------------------------------------|-------------|
| Global Warming Potential for R449A | 1397 | Global Warming Potential for R449A | 1397 |
| Carbon dioxide equivalent t | 0.265 | Carbon dioxide equivalent t | 0.265 |
| Pump capacity flow rate l/min | 8 ... 27 | Pump capacity flow rate l/min | 8 ... 27 |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | Pump capacity flow pressure bar | 0.1 ... 0.7 |

200-230V/50-60Hz (CN Plug)

| 200V/50Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| 200V/60Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 1.5 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |


| 230V/50Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 2 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

| 230V/60Hz | | | | | | | |
|------------------------------------|-------------|----|------|------|------|------|------|
| Heating capacity kW | 2 | | | | | | |
| Cooling capacity (Ethanol) | | | | | | | |
| °C | 20 | 10 | 0 | -10 | -20 | -30 | -40 |
| kW | 1 | 1 | 0.96 | 0.73 | 0.51 | 0.25 | 0.11 |
| Viscosity max. cST | 50 | | | | | | |
| Refrigerant | R449A | | | | | | |
| Filling volume g | 190 | | | | | | |
| Global Warming Potential for R449A | 1397 | | | | | | |
| Carbon dioxide equivalent t | 0.265 | | | | | | |
| Pump capacity flow rate l/min | 8 ... 27 | | | | | | |
| Pump capacity flow pressure bar | 0.1 ... 0.7 | | | | | | |

All Benefits



ATC.
Absolute Temperature Calibration, 1-point calibration (CD).



Condensation protection.
Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.



Handle with ease.
Makes day-to-day work easy. Comfortably move your JULABO Circulator around by using the ergonomic handles (front and rear).




Internal. External.
The pump is controlled via a lever located directly below the display. Easily change between internal and external circulation.



Mobile.
Extra easy handling. Integrated castors for easy repositioning of refrigerated circulators.



Safety.
CORIO CD and CP comply with Class III (FL) according to DIN 12876-1 and switches off automatically in case of high temperature or low liquid level alarm.



Solid.
Minimized energy loss through high-quality insulation.



Space saving. Free up space.
Place your JULABO Circulator right next to an application, another unit, or wall. That saves space. This is made possible by eliminating vents and connections on the sides.



Stable.
Rubber feet allow for a secured footing of your CORIO to prevent damage to your laboratory equipment.



Tidy.
The special drain tap for easy draining of bath fluids without tools.



Touching permitted.
Optimum safety. The ergonomic plastic handle protects your fingers from hot surfaces.




100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Timer. Integrated.
CORIO circulators include an integrated timer function. When the set time has elapsed, a signal sounds and the device switches off. Setting range: 0 ... 999 minutes.



Connection. Easy.
Inclined pump connections (M16×1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



Brilliant.
Very bright display makes it easy to read even from a distance.



Everything at the front.
All operating controls and safety functions are accessed easily and comfortably from the front.



Exact.
You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO precise and perfect.



Locked in.
The lockable power plug guarantees safe connection. More process safety.



Switch on. And off you go.
Intelligent operating concept. Ready for operation with just a few quick and easy steps.



Early warning system for low liquid level
Maximum safety for applications, optical and audible alarm, allows user to refill bath fluid before the unit shuts down



Powerful. Adjustable.
Strong pressure pump, continuously adjustable.



Early warning system for low liquid level.
Maximum safety for your application. Optical and audible alarm allows user to refill bath fluid in time.



Connectivity.
Remote control made easy. CORIO CP circulators feature a USB connection and RS232 interface.