

F25-HL HighTech HL Refrigerated - Heating Circulator

The top-of-the-line models with HL circulators offer professional technology and maximum functionality. The additional LCD dialog display interactively assists the user in setting circulator parameters. Intelligent Cascade Control (ICC) and Temperature Control Features (TCF) ensure optimal control behavior. HL circulators also have a Stakei connection.

Your advantages

- VFD COMFORT DISPLAY
- LCD DIALOG DISPLAY backlit for convenient interactive operation
- Keypad for setpoints, warning/safety values and menu functions
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- TCF Temperature Control Features to optimize the control behavior
- ATC3 3-Point-Calibration
- Pt100 External sensor connection for measurement and control
- SMART PUMP, electronically adjustable pump stages
- Adjustable pressure and suction pump
- Adjustable high temperature cut-out, visible via display
- Active Cooling Control
- RS232/RS485 interface for online communication
- Optional: analogue interfaces
- Integrated programmer for 6 x 60 program steps
- Connections for solenoid valve and HSP booster pump



Technical data

| | | | |
|-----------------------------------|--|------------------------------------|-------------------------|
| Available voltage versions | | Bath | |
| Order No. | 9 312 625 | Bath cover | integrated |
| Available voltage versions: | | Usable bath opening cm (W x L / D) | 12 x 14 / 14 |
| 9 312 625.01 | 100V/50-60Hz (Nema N5-15 Plug) | | |
| 9 312 625.02 | 115V/60Hz (Nema N5-15 Plug) | | |
| 9 312 625.03 | 230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F) | | |
| 9 312 625.04 | 230V/50Hz (UK Plug Type BS1363A) | | |
| 9 312 625.05 | 230V/50Hz (CH Plug Type SEV 1011) | | |
| 9 312 625.33 | 230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F) | | |
| Cooling | | Other | |
| Cooling of compressor | 1-stage Air | Sound pressure level dbA | 49 |
| | | Classification | Classification III (FL) |
| | | IP Code | IP 21 |
| | | Pump type | Immersion Pump |
| Electronics | | Dimensions and volumes | |
| Digital interface | Profibus optional | Weight kg | 32 |
| External pt100 sensor connection | integrated | Barbed fittings inner diameter | 8/12 mm |
| Integrated programmer | 6x60 steps | Dimensions cm (W x L x H) | 23 x 42 x 64 |
| Temperature control | ICC | Filling volume l | 3 ... 4.5 |
| Absolute temperature calibration | 3 Point Calibration | Pump connections | M16x1 male |
| Temperature display | VFD | | |

| Cooling capacity (Ethanol) | | | |
|------------------------------------|-------------|-----|------|
| °C | 20 | 0 | -20 |
| kW | 0.26 | 0.2 | 0.06 |
| Viscosity max. cST | 70 | | |
| Refrigerant | R134a | | |
| Filling volume g | 84 | | |
| Global Warming Potential for R134a | 1430 | | |
| Carbon dioxide equivalent t | 0.12 | | |
| Pump capacity flow rate l/min | 22 ... 26 | | |
| Pump capacity flow pressure bar | 0.4 ... 0.7 | | |
| Maximum suction bar | 0.2 ... 0.4 | | |

230V/50Hz (UK Plug Type BS1363A)

| 230V/50Hz | | | |
|------------------------------------|-------------|-----|------|
| Heating capacity kW | 2 | | |
| Cooling capacity (Ethanol) | | | |
| °C | 20 | 0 | -20 |
| kW | 0.26 | 0.2 | 0.06 |
| Viscosity max. cST | 70 | | |
| Refrigerant | R134a | | |
| Filling volume g | 84 | | |
| Global Warming Potential for R134a | 1430 | | |
| Carbon dioxide equivalent t | 0.12 | | |
| Pump capacity flow rate l/min | 22 ... 26 | | |
| Pump capacity flow pressure bar | 0.4 ... 0.7 | | |
| Maximum suction bar | 0.2 ... 0.4 | | |

230V/50Hz (CH Plug Type SEV 1011)

| 230V/50Hz | | | |
|------------------------------------|-------------|-----|------|
| Heating capacity kW | 2 | | |
| Cooling capacity (Ethanol) | | | |
| °C | 20 | 0 | -20 |
| kW | 0.26 | 0.2 | 0.06 |
| Viscosity max. cST | 70 | | |
| Refrigerant | R134a | | |
| Filling volume g | 84 | | |
| Global Warming Potential for R134a | 1430 | | |
| Carbon dioxide equivalent t | 0.12 | | |
| Pump capacity flow rate l/min | 22 ... 26 | | |
| Pump capacity flow pressure bar | 0.4 ... 0.7 | | |
| Maximum suction bar | 0.2 ... 0.4 | | |

230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)

| 230V/50Hz | | 230V/60Hz | |
|---------------------|---|---------------------|---|
| Heating capacity kW | 2 | Heating capacity kW | 2 |

| Cooling capacity (Ethanol) | | | | Cooling capacity (Ethanol) | | | |
|------------------------------------|-------------|-----|------|------------------------------------|-------------|-----|------|
| °C | 20 | 0 | -20 | °C | 20 | 0 | -20 |
| kW | 0.26 | 0.2 | 0.06 | kW | 0.26 | 0.2 | 0.06 |
| Viscosity max. cST | 70 | | | Viscosity max. cST | 70 | | |
| Refrigerant | R134a | | | Refrigerant | R134a | | |
| Filling volume g | 84 | | | Filling volume g | 84 | | |
| Global Warming Potential for R134a | 1430 | | | Global Warming Potential for R134a | 1430 | | |
| Carbon dioxide equivalent t | 0.12 | | | Carbon dioxide equivalent t | 0.12 | | |
| Pump capacity flow rate l/min | 22 ... 26 | | | Pump capacity flow rate l/min | 22 ... 26 | | |
| Pump capacity flow pressure bar | 0.4 ... 0.7 | | | Pump capacity flow pressure bar | 0.4 ... 0.7 | | |
| Maximum suction bar | 0.2 ... 0.4 | | | Maximum suction bar | 0.2 ... 0.4 | | |

All Benefits



JULABO. Quality.
Highest standards of quality for a long product life.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



Connection of additional equipment
Stakei connections for solenoid valve, HSP booster pump and HST booster heater



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines



Condensation and ice protection
A heated cover plate prevents condensation or ice build-up in the bath