

F32-HE Refrigerated - Heating Circulator

The HighTech Series features refrigerated heating /circulators with innovative technology for sophisticated applications. The instruments provide powerful, electronically adjustable pressure and suction pumps.

The instruments can be used for internal as well as external temperature control applications of closed and open systems.

Your advantages

- VFD COMFORT DISPLAY
- Keypad for setpoints, warning/safety values and menu functions
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- ATC3 3-Point-Calibration
- Pt100 External sensor connection for measurement and control
- SMART PUMP, electronically adjustable pump stages
- Adjustable pressure and suction pump
- Adjustable high temperature cut-out, visible via display
- RS232 interface for online communication
- Optional: analogue interfaces
- Integrated programmer for 10 program steps
- Active Cooling Control



Technical data

Available voltage versions		Bath	
Order No.	9 212 632	Bath cover	integrated
Available voltage versions:		Usable bath opening cm (W x L / D)	18 x 12 / 15
9 212 632.01	100V/50-60Hz (Nema N5-15 Plug)		
9 212 632.02	115V/60Hz (Nema N5-15 Plug)		
9 212 632.33	230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9 212 632.05	230V/50-60Hz (CH Plug Type SEV 1011)		
9 212 632.04	230V/50-60Hz (UK Plug Type BS1363A)		
Cooling		Other	
Cooling of compressor	1-stage Air	Sound pressure level dbA	53
		Classification	Classification III (FL)
		IP Code	IP 21
		Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Digital interface	Profibus optional	Weight kg	38
External pt100 sensor connection	integrated	Barbed fittings inner diameter	8/12 mm
Integrated programmer	1x10 steps	Dimensions cm (W x L x H)	31 x 42 x 66
Temperature control	ICC	Filling volume l	5.5 ... 8
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values			
Setting the resolution of the temperature display °C	0.01		

Working temperature range °C	-35 ... +200
Temperature stability °C	±0.01
Temperature stability external °C	±0.01 ... ±0.2
Ambient temperature °C	+5.0 ... +40.0
Temperature display resolution °C	0.01

Performance values

100V/50-60Hz (Nema N5-15 Plug)

100V/50Hz		100V/60Hz	
Heating capacity kW	0.8	Heating capacity kW	0.8
Cooling capacity (Ethanol)		Cooling capacity (Ethanol)	
°C	20 0 -20 -30	°C	20 0 -20 -30
kW	0.45 0.39 0.15 0.06	kW	0.45 0.39 0.15 0.06
Viscosity max. cST	70	Viscosity max. cST	70
Refrigerant	R134a	Refrigerant	R134a
Filling volume g	166	Filling volume g	166
Global Warming Potential for R134a	1430	Global Warming Potential for R134a	1430
Carbon dioxide equivalent t	0.237	Carbon dioxide equivalent t	0.237
Pump capacity flow rate l/min	22 ... 26	Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7	Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4	Maximum suction bar	0.2 ... 0.4

115V/60Hz (Nema N5-15 Plug)

115V/60Hz	
Heating capacity kW	1
Cooling capacity (Ethanol)	
°C	20 0 -20 -30
kW	0.45 0.39 0.15 0.06
Viscosity max. cST	70
Refrigerant	R134a
Filling volume g	166
Global Warming Potential for R134a	1430
Carbon dioxide equivalent t	0.237
Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4

230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz		230V/60Hz	
Heating capacity kW	2	Heating capacity kW	2
Cooling capacity (Ethanol)		Cooling capacity (Ethanol)	
°C	20 0 -20 -30	°C	20 0 -20 -30
kW	0.45 0.39 0.15 0.06	kW	0.45 0.39 0.15 0.06

Viscosity max. cST	70	Viscosity max. cST	70
Refrigerant	R134a	Refrigerant	R134a
Filling volume g	166	Filling volume g	166
Global Warming Potential for R134a	1430	Global Warming Potential for R134a	1430
Carbon dioxide equivalent t	0.237	Carbon dioxide equivalent t	0.237
Pump capacity flow rate l/min	22 ... 26	Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7	Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4	Maximum suction bar	0.2 ... 0.4

230V/50-60Hz (CH Plug Type SEV 1011)

230V/50Hz						230V/60Hz					
Heating capacity kW						2					
Cooling capacity (Ethanol)						Cooling capacity (Ethanol)					
°C	20	0	-20	-30		°C	20	0	-20	-30	
kW	0.45	0.39	0.15	0.06		kW	0.45	0.39	0.15	0.06	
Viscosity max. cST	70					Viscosity max. cST	70				
Refrigerant	R134a					Refrigerant	R134a				
Filling volume g	166					Filling volume g	166				
Global Warming Potential for R134a	1430					Global Warming Potential for R134a	1430				
Carbon dioxide equivalent t	0.237					Carbon dioxide equivalent t	0.237				
Pump capacity flow rate l/min	22 ... 26					Pump capacity flow rate l/min	22 ... 26				
Pump capacity flow pressure bar	0.4 ... 0.7					Pump capacity flow pressure bar	0.4 ... 0.7				
Maximum suction bar	0.2 ... 0.4					Maximum suction bar	0.2 ... 0.4				

230V/50-60Hz (UK Plug Type BS1363A)

230V/50Hz						230V/60Hz					
Heating capacity kW						2					
Cooling capacity (Ethanol)						Cooling capacity (Ethanol)					
°C	20	0	-20	-30		°C	20	0	-20	-30	
kW	0.45	0.39	0.15	0.06		kW	0.45	0.39	0.15	0.06	
Viscosity max. cST	70					Viscosity max. cST	70				
Refrigerant	R134a					Refrigerant	R134a				
Filling volume g	166					Filling volume g	166				
Global Warming Potential for R134a	1430					Global Warming Potential for R134a	1430				
Carbon dioxide equivalent t	0.237					Carbon dioxide equivalent t	0.237				
Pump capacity flow rate l/min	22 ... 26					Pump capacity flow rate l/min	22 ... 26				
Pump capacity flow pressure bar	0.4 ... 0.7					Pump capacity flow pressure bar	0.4 ... 0.7				
Maximum suction bar	0.2 ... 0.4					Maximum suction bar	0.2 ... 0.4				

All Benefits



JULABO. Quality.
Highest standards of quality for a long product life.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines