

FCW2500T Chiller

FC recirculating coolers with a particularly powerful pump and Pt100 connection are preferably used for precise temperature control of large-volume external applications. They can be integrated into process control systems via the permanently integrated analog connection.

Your advantages

- Adjustable ratio for feed/return temperatures
- Easy filling system located at the front
- Activation of pump for filling
- Bright MULTI-DISPLAY (LED)
- Upper and lower temperature warning functions with interval tone
- Integrated freezing protection and dry-running protection
- Rapid and easy operation via seamless, splash-proof keypad
- Liquid level indication on the front
- Self-test, reciprocal sensor monitoring, pump motor and compressor overload protection
- Complete shut-down with audible signal in case of an alarm
- Removable venting grid for simplified removal of dust
- RS232 interface for PC connection
- High temperature stability
- Integrated heater with 1.2 kW capacity
- Pressure Indicator
- Connections for external Pt100 sensor
- Analog Connections for programming (0..10V / 0...24mA) and temperature recorder (0V = 0°C)

Technical data

Available voltage versions		Bath	
Order No.	9 601 256	Bath tank	Stainless steel
Available voltage versions:			
9 601 256.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9 601 256.04	230V/50Hz (UK Plug Type BS1363A)		
9 601 256.13	230V/60Hz (Nema N6-20 Plug)		
Cooling		Other	
Cooling of compressor	1-stage Water	Sound pressure level dbA	53
Cooling water pressure max. bar	6	Classification	Classification III (FL)
Cooling water difference pressure bar	3.5 ... 6	IP Code	IP 21
		Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Digital interface	RS232	Weight kg	74
External pt100 sensor connection	integrated	Cooling Water Connection in	G $\frac{3}{4}$
Temperature control	PID1	Barbed fittings inner diameter	8/12 mm
Temperature display	2x LED	Dimensions cm (W x L x H)	46 x 61 x 49
Temperature setting	Keypad	Filling volume l	8 ... 11
		Pump connections	M16x1 male

Temperature values

Working temperature range °C -25 ... +80

Temperature stability °C ± 0.2

Ambient temperature °C 5 ... 40

Temperature display resolution °C 0.1

Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz						
Heating capacity kW	1.2					
Cooling capacity (Water Glycol)						
°C	20	10	5	0	-10	-20
kW	2.5	2	1.8	1.4	0.8	0.25
Refrigerant	R449A					
Filling volume g	450					
Global Warming Potential for R449A	1397					
Carbon dioxide equivalent t	0.629					
Pump capacity flow rate l/min	28					
Pump capacity flow pressure bar	3.5					

230V/50Hz (UK Plug Type BS1363A)

230V/50Hz						
Heating capacity kW	1.2					
Cooling capacity (Water Glycol)						
°C	20	10	5	0	-10	-20
kW	2.5	2	1.8	1.4	0.8	0.25
Refrigerant	R449A					
Filling volume g	450					
Global Warming Potential for R449A	1397					
Carbon dioxide equivalent t	0.629					
Pump capacity flow rate l/min	28					
Pump capacity flow pressure bar	3.5					

230V/60Hz (Nema N6-20 Plug)

230V/60Hz						
Heating capacity kW	1.2					
Cooling capacity (Water Glycol)						
°C	20	10	5	0	-10	-20
kW	2.5	2	1.8	1.4	0.8	0.25
Refrigerant	R449A					
Filling volume g	450					
Global Warming Potential for R449A	1397					
Carbon dioxide equivalent t	0.629					
Pump capacity flow rate l/min	28					
Pump capacity flow pressure bar	3.5					

All Benefits



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



For higher demands
PID Temperature control with drift compensation and adjustable parameters, improved temperature stability for external applications, temperature stability ± 0.01 °C internal, $< \pm 0.1$ °C external.



Connection of additional equipment
Stakei connections for solenoid valve, HSP booster pump and HST booster heater



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function