

FLW2006 Powerful recirculating cooler

The powerful FL models are suitable for a wide range of cooling tasks in industrial environments, such as removal of large process heat. 2 variants: Air-cooled (FL) and water-cooled (FLW).



Your advantages

- Ergonomic design and easy operation
- Splash-proof keypad
- Large, bright LED display
- Permissible temperature in return line +80°C
- Easy filling from the top with hinged protective lid
- Low liquid level protection with optical and audible alarm signal
- Integrated stainless steel bath tanks
- Removable ventilation grid
- Front drain
- No side vents, instruments can be placed right next to other equipment
- RS232 interface for PC connection
- IP class according to IEC 60529: 21
- Alarm output, potential-free change-over contact (max. 30 VA)
- Pressure Indicator
- By-pass valve to adjust pump pressure

Technical data

Available voltage versions		Bath	
Order No.	9 676 200	Bath tank	Stainless steel
Available voltage versions:			
9 676 200.16	230V/3PPE/60Hz (Without Plug)		
9 676 200.07	400V/3PNPE/50Hz (Plug 32A CEE)		
Cooling		Other	
Cooling of compressor	1-stage Water	Sound pressure level dbA	69
Cooling water pressure max. bar	6	Classification	Classification I (NFL)
Cooling water difference pressure bar	2 ... 6	IP Code	IP 21
Cooling water consumption l/min	24	Pump type	Centrifugal Pump
Electronics		Dimensions and volumes	
Temperature control	PID1	Weight kg	341
Temperature display	LED	Cooling Water Connection in	G $\frac{3}{4}$
Temperature setting	Keypad	Barbed fittings inner diameter	1"
		Dimensions cm (W x L x H)	95 x 115 x 161
		Filling volume l	15 ... 37
		Pump connections	G1 $\frac{1}{4}$ " male
Temperature values			
Setting the resolution of the temperature display °C	0.1		
Return flow temperature max. °C	80		
Working temperature range °C	-25 ... +40		
Temperature stability °C	±0.5		
Ambient temperature °C	5 ... 40		
Temperature display resolution °C	0.1		

Performance values

230V/3PPE/60Hz (Without Plug)

230V/3PPE/60Hz					
Cooling capacity (Water Glycol)					
°C	20	10	0	-10	-20
kW	20	15	12	7	3
Refrigerant	R404A				
Filling volume g	2500				
Global Warming Potential for R404A	3922				
Carbon dioxide equivalent t	9.805				
Pump capacity flow rate l/min	80				
Pump capacity flow pressure bar	0.8 ... 6				

400V/3PNPE/50Hz (Plug 32A CEE)

400V/3PNPE/50Hz					
Cooling capacity (Water Glycol)					
°C	20	10	0	-10	-20
kW	20	15	12	7	3
Refrigerant	R452A				
Filling volume g	2750				
Global Warming Potential for R452A	2140				
Carbon dioxide equivalent t	5.885				
Pump capacity flow rate l/min	80				
Pump capacity flow pressure bar	0.8 ... 6				

All Benefits



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Precise
PID Temperature control with set control
parameters, temperature stability $\pm 0.02 \dots \pm 0.2$
°C