

FLW2506 Powerful model in tower version

The FL models shown here have higher cooling capacity, powerful circulating pumps, and internal bath volumes of up to 30 liters. 2 variants: Air-cooled (FL) and water-cooled (FLW).



Your advantages

- Ergonomic design and easy operation
- Splash-proof keypad
- Large, bright LED display
- Reliable Microprocessor PID temperature control
- Precise PID temperature control
- Powerful immersion pumps, suitable for continuous operation
- Permissible temperature in return line +80°C
- Easy filling from the top with hinged protective lid
- Low liquid level protection with optical and audible alarm signal
- Integrated stainless steel bath tanks
- Removable ventilation grid
- Front drain
- No side vents, instruments can be placed right next to other equipment
- RS232 interface for PC connection
- IP class according to IEC 60529: 21
- Alarm output, potential-free change-over contact (max. 30 VA)
- Pressure Indicator
- By-pass valve to adjust pump pressure

Technical data

Available voltage versions		Bath	
Order No.	9 676 025	Bath tank	Stainless steel
Available voltage versions:			
9 676 025.13	230V/60Hz (Nema N6-20 Plug)		
9 676 025.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)		
Cooling		Other	
Cooling of compressor	1-stage Water	Sound pressure level dbA	61
Cooling water pressure max. bar	6	Classification	Classification I (NFL)
Cooling water difference pressure bar	2 ... 6	IP Code	IP 21
Cooling water consumption l/min	4.1	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Temperature control	PID1	Weight kg	160
Temperature display	LED	Cooling Water Connection in	G $\frac{3}{4}$
Temperature setting	Keypad	Barbed fittings inner diameter	1"
		Dimensions cm (W x L x H)	60 x 76 x 115
		Filling volume l	24 ... 30
		Pump connections	G1 $\frac{1}{4}$ " male
Temperature values			
Setting the resolution of the temperature display °C	0.1		
Return flow temperature max. °C	80		
Working temperature range °C	-15 ... +40		
Temperature stability °C	±0.5		

Ambient temperature °C	5 ... 40
Temperature display resolution °C	0.1

Performance values

230V/60Hz (Nema N6-20 Plug)

208V/60Hz					230V/60Hz				
Cooling capacity (Water Glycol)					Cooling capacity (Water Glycol)				
°C	20	10	0	-10	°C	20	10	0	-10
kW	2.5	1.9	1	0.3	kW	2.5	1.9	1	0.3
Refrigerant	R404A				Refrigerant	R404A			
Filling volume g	720				Filling volume g	720			
Global Warming Potential for R404A	3922				Global Warming Potential for R404A	3922			
Carbon dioxide equivalent t	2.824				Carbon dioxide equivalent t	2.824			
Pump capacity flow rate l/min	60				Pump capacity flow rate l/min	60			
Pump capacity flow pressure bar	0.5 ... 6				Pump capacity flow pressure bar	0.5 ... 6			

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz				
Cooling capacity (Water Glycol)				
°C	20	10	0	-10
kW	2.5	1.9	1	0.3
Refrigerant	R452A			
Filling volume g	940			
Global Warming Potential for R452A	2140			
Carbon dioxide equivalent t	2.012			
Pump capacity flow rate l/min	60			
Pump capacity flow pressure bar	0.5 ... 6			

All Benefits



Precise
 PID Temperature control with set control parameters, temperature stability $\pm 0.02 \dots \pm 0.2$ °C



JULABO. Quality.
 Highest standards of quality for a long product life.



Green technology.
 Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
 11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.