

FLW4003 Powerful model in tower version

The FL models shown here have higher cooling capacity, powerful circulating pumps, and internal bath volumes of up to 30 liters. 2 variants: Air-cooled (FL) and water-cooled (FLW).



Your advantages

- Ergonomic design and easy operation
- Splash-proof keypad
- Large, bright LED display
- Reliable Microprocessor PID temperature control
- Precise PID temperature control
- Powerful immersion pumps, suitable for continuous operation
- Permissible temperature in return line +80°C
- Easy filling from the top with hinged protective lid
- Low liquid level protection with optical and audible alarm signal
- Integrated stainless steel bath tanks
- Removable ventilation grid
- Front drain
- No side vents, instruments can be placed right next to other equipment
- RS232 interface for PC connection
- IP class according to IEC 60529: 21
- Alarm output, potential-free change-over contact (max. 30 VA)
- Pressure Indicator
- By-pass valve to adjust pump pressure

Technical data

Available voltage versions		Bath	
Order No.	9 673 040	Bath tank	Stainless steel
Available voltage versions:			
9 673 040.16	230V/3PPE/60Hz (Without Plug)		
9 673 040.07	400V/3PNPE/50Hz (Plug 16A CEE)		
Cooling		Other	
Cooling of compressor	1-stage Water	Sound pressure level dbA	65
Cooling water pressure max. bar	6	Classification	Classification I (NFL)
Cooling water difference pressure bar	2 ... 6	IP Code	IP 21
Cooling water consumption l/min	6.6	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Temperature control	PID1	Weight kg	144
Temperature display	LED	Cooling Water Connection in	G $\frac{3}{4}$
Temperature setting	Keypad	Barbed fittings inner diameter	$\frac{3}{4}$ "
		Dimensions cm (W x L x H)	60 x 76 x 115
		Filling volume l	24 ... 30
		Pump connections	G $\frac{3}{4}$ "
Temperature values			
Setting the resolution of the temperature display °C	0.1		
Return flow temperature max. °C	80		
Working temperature range °C	-20 ... +40		
Temperature stability °C	±0.5		

Ambient temperature °C	5 ... 40
Temperature display resolution °C	0.1

Performance values

230V/3PPE/60Hz (Without Plug)

230V/3PPE/60Hz					
Cooling capacity (Water Glycol)					
°C	20	10	0	-10	-20
kW	4.3	3	2.2	1.3	0.45
Refrigerant	R404A				
Filling volume g	700				
Global Warming Potential for R404A	3922				
Carbon dioxide equivalent t	2.745				
Pump capacity flow rate l/min	40				
Pump capacity flow pressure bar	0.5 ... 3				

400V/3PNPE/50Hz (Plug 16A CEE)

400V/3PNPE/50Hz					
Cooling capacity (Water Glycol)					
°C	20	10	0	-10	-20
kW	4.3	3	2.2	1.3	0.45
Refrigerant	R452A				
Filling volume g	1100				
Global Warming Potential for R452A	2140				
Carbon dioxide equivalent t	2.354				
Pump capacity flow rate l/min	40				
Pump capacity flow pressure bar	0.5 ... 3				

All Benefits



Precise
 PID Temperature control with set control parameters, temperature stability $\pm 0.02 \dots \pm 0.2$ °C



JULABO. Quality.
 Highest standards of quality for a long product life.



Green technology.
 Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
 11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.