

FPW50-HL HighTech HL Refrigerated - Heating Circulator

The top-of-the-line models with HL circulators offer professional technology and maximum functionality. The additional LCD dialog display interactively assists the user in setting circulator parameters. Intelligent Cascade Control (ICC) and Temperature Control Features (TCF) ensure optimal control behavior. HL circulators also have a Stakei connection.



Your advantages

- VFD COMFORT DISPLAY
- LCD DIALOG DISPLAY backlit for convenient interactive operation
- Keypad for setpoints, warning/safety values and menu functions
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- TCF Temperature Control Features to optimize the control behavior
- ATC3 3-Point-Calibration
- Pt100 External sensor connection for measurement and control
- SMART PUMP, electronically adjustable pump stages
- Adjustable pressure and suction pump
- Adjustable high temperature cut-out, visible via display
- Active Cooling Control
- RS232/RS485 interface for online communication
- Optional: analogue interfaces
- Integrated programmer for 6 x 60 program steps
- Connections for solenoid valve and HSP booster pump

Technical data

Available voltage versions		Bath	
Order No.	9 312 651	Bath cover	integrated
Available voltage versions:		Usable bath opening cm (W x L / D)	18 x 12 / 15
9 312 651.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)		
9 312 651.13	230V/60Hz (Nema N6-20 Plug)		
Cooling		Other	
Cooling of compressor	1-stage Water	Classification	Classification III (FL)
Cooling water pressure max. bar	6 ... 6	IP Code	IP 21
Cooling water difference pressure bar	3.5 ... 6	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Digital interface	Profibus optional	Weight kg	57
External pt100 sensor connection	integrated	Cooling Water Connection in	G $\frac{3}{4}$
Integrated programmer	6x60 steps	Barbed fittings inner diameter	8/12 mm
Temperature control	ICC	Dimensions cm (W x L x H)	42 x 49 x 72
Absolute temperature calibration	3 Point Calibration	Filling volume l	8
Temperature display	VFD	Pump connections	M16x1 male
Temperature setting	Keypad		
Temperature values			
Setting the resolution of the temperature display °C	0.01		
Working temperature range °C	-50 ... +200		
Temperature stability °C	±0.01		
Ambient temperature °C	+5.0 ... +40.0		

Temperature display resolution °C 0.01

Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

230V/50Hz					
Heating capacity kW	2				
Cooling capacity (Ethanol)					
°C	20	0	-20	-30	-40
kW	0.9	0.8	0.49	0.26	0.11
Viscosity max. cST	70				
Refrigerant	R452A				
Filling volume g	480				
Global Warming Potential for R452A	2140				
Carbon dioxide equivalent t	1.027				
Pump capacity flow rate l/min	22 ... 26				
Pump capacity flow pressure bar	0.4 ... 0.7				
Maximum suction bar	0.2 ... 0.4				

230V/60Hz (Nema N6-20 Plug)

230V/60Hz					
Heating capacity kW	2				
Cooling capacity (Ethanol)					
°C	20	0	-20	-30	-40
kW	0.9	0.8	0.4	0.16	0.03
Viscosity max. cST	70				
Refrigerant	R449A				
Filling volume g	480				
Global Warming Potential for R449A	1397				
Carbon dioxide equivalent t	0.671				
Pump capacity flow rate l/min	22 ... 26				
Pump capacity flow pressure bar	0.4 ... 0.7				
Maximum suction bar	0.2 ... 0.4				

All Benefits



JULABO. Quality.
Highest standards of quality for a long product life.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



Connection of additional equipment
Stake connections for solenoid valve, HSP booster pump and HST booster heater



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



Control from the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines



Condensation and ice protection
A heated cover plate prevents condensation or ice build-up in the bath