

Hydraulically sealed Refrigerated Heating Circulator with air- and water-cooled refrigerating unit. Evaporator and housing made of stainless steel. With atmospheric open expansion tank and optical level indicator. As well as for externally closed and also externally open applications.

High system performance (watt/litre) due to minimized internal volume. No HTF vapour and no moisture absorption because the expansion tank is thermally passive. For external open baths the expansion tank will be blocked off. This means that the thermostat is atmospherically sealed and can be located below or above the level of the application.

Pilot ONE:

The new Pilot ONE controller with pioneering technology and advanced control functions brings numerous advantages to routine work. The extensive features list includes a brilliant 5,7" TFT touchscreen display, USB and network connections, an integrated technical glossary and language support in 13 languages (EN, DE, FR, IT, ES, RU, CN, PT, JP, CZ, PL, KO, TR). The Pilot ONE has a convenient navigation system with easily remembered icons and menu categories which are colour sorted to make routine work simpler. Thanks to a favourites menu and One-Click operator guidance all important information is always just a few keystrokes away. Software wizards also help you to set up, ensuring correct settings. The USB port allows connection of the system to a PC or notebook. Together with the Spy software, requirements such as remote control or data transmission are easily achieved in a cost-effective manner. Network integration is easy with the internet port.

further functions:

E-grade Professional installed as standard, TAC (True Adaptive Control) - self optimising internal and cascade control, selectable temperature control mode (Internal/Process), programmer with 10 programs (max. 100 steps), ramp function (linear and non-linear), 5 point calibration, scalable graphic display, favourites menu, display resolution 0,01 K, integrated technical glossary, 2nd set point, user menus (Administrator level), calendar start, wallpaper selection.

3-2-2 warranty - registration required.

Technical data according to DIN 12876

Operating temperature range	-45...250 °C
Temperature stability at -10°C	0,01 K
temperature set point / display	5,7" colour Touchscreen
Resolution of display	0,01 K
Internal temperature sensor	Pt100
Sensor external connection	Pt100
Interface digital	Ethernet, USB (Host u. Device), RS232
digital input	ECS ONE
digital output	POKO ONE
Alarm message	optic, acoustic, relay
Safety classification	Class III / FL
Heating power	3 kW
Cooling power with	Thermooil
at 250°C	0,7 kW
at 200°C	0,7 kW
at 100°C	0,7 kW
Cooling power with	Ethanol
at 0°C	0,7 kW
at -20°C	0,4 kW
at -40°C	0,06 kW
Refrigeration machine	luft- und wassergekühlt, natürliches KM
Refrigerant (ASHRAE, GHS)	R1270 (A3, H220)
Refrigerant quantity	0,15 kg
Gas warning sensor	without
Circulation pump:	
max. delivery	55 l/min
max. delivery pressure	0.9 bar
Pump connection	M24x1,5 male
max. permissible kin. viscosity	50 mm ² /s
Cooling water connection	G1/2 male
Consumption at water 15°C, flow 0°C	66 l/h
Consumption at water 15°C, flow -20°C	30 l/h
Consumption at water 25°C, flow 0°C	102 l/h



Order-No.: 1000.0040.01

Technical data according to DIN 12876

Verbrauch b. Wasser 25°C, Vorlauf -20°C	54 l/h
min. cooling water differential pressure	0,5 bar
max. cooling water pressure	6 bar
min. filling capacity	1,5 l
Filling capacity expansion tank	2,8 l
Overall dimensions WxDxH **	426x327x631 mm
Net weight	56 kg
sound pressure level +/- 4 dB(A)	62 dB(A)
Power supply requirement	230V 1~ 50Hz
max. current	15,9 A
Fuse	16 A
Degree of Protection	IP20
min. ambient temperature	5 °C
max. ambient temperature	40 °C

from Serial-No.:

351213

1.0/19

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Accessories and periphery: mini-USB cable #54949*, E-grade "Professional" #9496*, Adaptor M16x1 male to M24x1,5 female*, E-grade "Explore" #10495, RS232 adapter cable #55018, SpyLight-Software, Com.G@te Namur, PC-Com.G@te-cabel, Holder for Com.G@te # 10019; Com.G@te-extension cable: upon request, Thermofluid, external pressure sensor, metal hoses M16x1 or M24x1,5, external sensor, connecting cable, isolation sleeve for external open applications, float switch in sight glass for extended security.

Note: Pump connections: Bore shape Y (60°) according to DIN 3863, pipework/flexible tempering hoses: Ball socket according to DIN 3863, sleeve nut according to DIN 3870.

* standard equipment

Output data valid for: Room temperature 20°C, cooling water inlet 15°C and 0,5 bar differential pressure between cooling water inlet and -outlet. This temperature control unit has been designed to operate with cooling water up to 20°C. As the cooling water temperature increases, drop in the cooling power should be expected, and also an increased cooling water flow rate possible. If the ambient temperature rises, the cooling capacity may drop. Materials used in the cooling water circuit include: copper, Stainless steel 1.4401, MS, PA, PPE, PTFE and EPDM. Please use suitable cooling water.

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Standard delivery conditions - Power cable configuration:

1. Single-phase devices (230V/115V) -> with cable and plug
2. Three-phase devices with current consumption less than 63A -> with cable, without plug
3. Three-phase devices with current consumption greater than 63A -> without cable, without plug

This equipment is compliant to US-SNAP and all applicable EU laws. The US-SNAP end-use for this equipment is the industrial process refrigeration. Certification by a Notified Body upon request.

** Please respect space requirements. See operating conditions at www.huber-online.com