New Generation Liquid Nitrogen Plants

CNP120 - Compact, Economic and Elegant

CNP120 arrives as a plug-and-liquify system with external compressor and chiller to lower the noise in the plant room. A fully integrated design and one button operation allows you to place CNP series liquifiers in the research labs or clean rooms. Its modular design takes a little space and allows you to extend your liquification capacity. Simply make the electrical connections and produce your own liquid nitrogen by a fully automated operation with a user friendly interface of its PLC controller. Operator only needs to replace the filters and perform routine checks between maintenance intervals of 13000 operating hours.



Production Rate ≥ 120 liter/day (≥ 128 l/day @23°C) **Electrical Options** 380/400/415VAC, 3Ph, 50Hz,

480VAC, 3 Ph, 60 Hz

Power Consumption (Steady State) 14kW @ 50Hz

16kW @ 60Hz

Dimensions 1245 mm (W) x 1820 mm (L) x 1388 mm (H)

Weight 650 kg (Empty) / 950 kg (Full) Suggested Installation Area 6m (W) x 3m (L) x 3m (H) Compressed Air Requirement ~15 m³/hour @7 bar Cooling Water Flow Rate 18 liters/min @ 4 bar

Cryocooler GM type cryocooler mounted on Dewar He, 99.995% purity @ 15-16.7bar (220-245psig) Compressor

Human Machine Interface 8" Color Graphic Touch Screen **Dewar Volume** 360 liters, 500 liter (optional)

Operating Pressure 2.0 bar

Dewar Level Control Capacitive level sensor

Features Easy installation, fully automatic start and stop operation by PLC which

> supports efficient troubleshooting, the monitor displays the operational status of the plant and the failures triggered by safety devices and sensors, single switch operation, control all components through the diagnostic screen, LN₂ transfer by one button, Automatic re-start after power failure.

Built-in Nitrogen Generator

≥ 99% **Purity Dew Point** up to -40°C Flow Rate 3.5 m³/hour **Ambient Temperature Range** +5°C to +50°C Maximum Altitude 3 000 meters Noise Level < 65 dB @ 1 meter

Standards CE Conformance, ISO 12100:2010, IEC60204-1, 2006/42/EC, 97/23/EC;

ISO9001:2015